

BuyBoard Quote

ASSOCIATED SUPPLY COMPANY, INC.

THE FOLLOWING DETAILS SHALL BE PROVIDED WITH ANY BUYBOARD PURCHASE ORDER (FAX PURCHASE ORDER TO 800-211-5454)

BuyBoard Vendor: ASSOCIATED SUPPLY COMPANY, INC.
Address: 6203 LONG DR, HOUSTON TX 77087
Phone: 713-649-0940
Fax: 713-649-5571

Prepared By: TIMOTHY GATES
Mobile: 281-627-5148
Email: TGATES@ASCOEQ.COM

Government Agency: GALVESTON PARKS BOARD

Date Prepared: 5/4/2022

Ship To: GALVESTON PARK BOARD

Bill To: GALVESTON PARK BOARD

Contacts' Name: LARRY JACKSON
Email: LJACKSON@GALVESTONPARKBOARD.ORG

Phone: 409-797-5105
Fax:

Product Description: LEEBOY 695B MOTOR GRADER CAB

BuyBoard Contract: 597-19

I. Price List Dated: 3/1/2022

Base Price: \$ 242,897.00

II: Base Bid Options (Itemized Below)

Table with 2 columns: Description and Price. Items include REAR-MOUNTED SCARIFIER (\$5,145.00), FOOT THROTTLE (\$1,253.00), F-N-R PEDAL (\$2,622.00), 11' MOLDBOARD (INCLUDED), CUMMINS TIER 4 FINAL DIESEL ENGINE (INCLUDED), LED FRONT MOLDBOARD LIGHTS (INCLUDED), LED REAR WORKING LIGHTS (INCLUDED). SUB-TOTAL: \$ 9,020.00

Table with 2 columns: Description and Price. This side of the table is currently blank.

Options List Price Total: \$ 9,020.00
\$ 251,917.00

III. SUB-TOTAL OF I & II

IV. BuyBoard Discount: 8.00% \$ 20,153.36

BUYBOARD CONTRACT PRICE: \$ 231,763.64

V: NON-BASE OPTIONS

Non-Base Options (%) = 0

Table with 2 columns: Description and Price. Items include LOCAL DELIVERY (\$850.00), FACTORY FREIGHT (\$3,200.00), PDI (\$650.00). SUB-TOTAL: \$ 4,700.00

Table with 2 columns: Description and Price. This side of the table is currently blank.

VI: UNPUBLISHED OPTIONS ADDED TO CONTRACT PRICE (SUBTOTAL OF COL1 & COL 2)

\$ 4,700.00

VII: TOTAL IV + VI

\$ 236,463.64

VIII: QUANTITY ORDERED UNITS: 1

\$ 236,463.64

IX: TRADE-IN OR OTHER CREDIT(S):

TOTAL: \$ 236,463.64

695B Motor Grader Specifications



Dimensions	<ul style="list-style-type: none"> - Length: 22' 3" - Width: 7' 8" - Height (w/ cab and beacon): 10' 2" - Wheel base: 16' 1" - Base weight: 16,000 lbs.
Engine	Cummins turbocharged diesel, Tier 4 Final – 130 hp
Capacities	<ul style="list-style-type: none"> - Fuel: 45 gallons - Hydraulic reservoir: 30 gallons
Moldboard	<ul style="list-style-type: none"> - 11' x 21" x 5/8" - Side shift: 3' left or right - Tilt: 30° - Ground clearance: 13" - Penetration: 1' 2" - Rotation: 64°
Drawbar	- 4" x 6" x 0.5" tube
Articulated Frame	- Steel channel, rectangular tubing, articulated 24" in each direction
Turning Radius	- 22' from center to outside front tire with frame articulated
Traction Drive	<ul style="list-style-type: none"> - Hydrostatic drive, 2-speed tandem axle - Working range: 0 to 10 mph - Travel range: 0 to 20 mph - Tandems oscillate a minimum of +/- 15°
Tires	<ul style="list-style-type: none"> - Six 15 x 19.5, TL, G-2 - 8-ply pneumatic tires
Brakes	<ul style="list-style-type: none"> - Foot operated primary and service brakes - Hydrostatic traction drive system includes secondary brakes - Spring apply, hydraulic release parking brakes automatically apply when ignition is in "off" position or if system pressure is lost
Rear Hitch	- 15-ton, heavy-duty, forged rear pintle hitch
Operator's Station	<ul style="list-style-type: none"> - Fully cushioned, adjustable suspension seat - Adjustable operator's pedestal - Choice ROPS/FOPS cab or ROPS/FOPS canopy

	<ul style="list-style-type: none"> - Cab includes air conditioning, heat, front and rear wiper, washer, defroster and radio/CD with speakers - Two external convex 7.5" diameter side mirrors, single rear view mirror - Color display with digital readouts: coolant and hydraulic oil temperature, fuel level, volt meter, tachometer, hour meter, DEF level, percent engine load, engine diagnostics
Operator's Controls	- Industry-standard control levers mounted to an adjustable operator's pedestal
Lighting	<ul style="list-style-type: none"> - Left and right-hand moldboard lift, front attachment lift, moldboard side shift, circle side shift, moldboard tilt, circle turn, articulation, front wheel lean and rear-mount scarifier control - Two rear LED working lights - Two front LED moldboard lights
Additional Standard Equipment:	<ul style="list-style-type: none"> - Two front headlights, signals, flashers - Two rear tail lights, signals - Amber LED strobe beacon - Back-up alarm - High temperature, low oil pressure shut down
Optional Equipment	<ul style="list-style-type: none"> - Horn - Slow moving vehicle sign - 12V DC power outlet - Mounting provisions for Topcon control system sensors - All-wheel drive - Cold weather engine package - Rear-mounted scarifier, includes 9 ripper shanks with teeth - 8' x 16" front blade, includes blade float control - Front blade mounted flip-down 4 shank scarifier - 8' X 30" front dozer blade, includes blade float control - Front-mounted V-bar scarifier, includes float control - 10' moldboard - 12' moldboard - Foot throttle - F-N-R pedal - Dead engine steering - Back-up/reverse camera with in cab color display - Circle side shift - Topcon ready options



ST Engineering LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300
www.LeeBoy.com



LeeBoy and the LeeBoy logo are registered trademarks of ST Engineering LeeBoy, Inc. Equipment model names, slogans and subsidiary logos appearing in this collateral may be registered trademarks or the trademarks of ST Engineering LeeBoy, Inc. The technical data contained herein is subject to change due to continuous engineering and development. Accordingly, LeeBoy reserves the right to modify at any time. © 2020 ST Engineering LeeBoy, Inc. All rights reserved. BR-2002.7-EN